

Printing date 01/09/2019 Version - No. 2 Reviewed on 01/09/2019

#### 1 Identification

• 1.1 Product identifier

• Trade name: MARVAC® 125

Article number:

® registered trademark of VACUUMSCHMELZE GmbH & Co. KG

• Material Safety Data Sheet - no.: SDB4

- Application of the substance / the mixture semi-finished products and parts
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

VACUUMSCHMELZE GmbH & Co.KG Grüner Weg 37 D-63450 Hanau

datasheet@vacuumschmelze.com

• Information department: Environmental Protection Department

• 1.4 Emergency telephone number: Tel. no.: (\*\*49) 6181/38-0 Emergency tel. no.: via (\*\*49) 6181/38-0

#### 2 Hazard(s) identification

#### 2.2 Classification (substance or mixture)

Classification according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

Our semi-finished and finished products constitute manufactured articles under the terms of the REACH Regulation (EC) No. 1907/2006.

For articles there is no obligation to classify acc. to CLP -Regulation.

#### • 2.2 Labelling according to Regulation (EC) No 1272/2008

Labelling according to Regulation (EC) No 1272/2008 (CLP-Regulation):

Not applicable

#### Additional VAC information:

#### In the case of dust-producing processing, we recommend observance of the following warnings :

#### Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure.

#### Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not eat, drink or smoke when using this product.

Avoid release to the environment.

Use personal protective equipment as required.

In case of inadequate ventilation wear respiratory protection.

Get medical advice/attention if you feel unwell.

#### • 2.3 Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

USA



Reviewed on 01/09/2019 Printing date 01/09/2019 Version - No. 2

Trade name: MARVAC® 125

(Contd. of page 1)

#### 3 Composition/information on ingredients

#### 3.2 Chemical characterization:

• Description: Metal in compact form

#### Dangerous components:

The classifications given below reflect the classification of each pure substance respectively and are intended for information only

The legal classifications of the pure substances (harmonized classification according to substance list of the Annex VI of the CLP Regulation) got complemented, insofar as additional substance-specific information from accessible data sources (e.g. TRGS 905, toxicological studies) for health hazards and / or physical hazards are

#### The concentration of cobalt might be $\geq 0.1\%$ (impurities)

\* = possible inpurities

F		
CAS: 7439-89-6 EINECS: 231-096-4	iron (compact form)	rest%
CAS: 7440-47-3 EINECS: 231-157-5	chromium	~ 13%
CAS: 7440-02-0 EINECS: 231-111-4 Index number: 028-002-00-7	nickel	~ 8%
CAS: 7439-98-7 EINECS: 231-107-2	molybdenum	< 1.5%
CAS: 7440-41-7 EINECS: 231-150-7 Index number: 004-001-00-7	beryllium  → Acute Tox. 3, H301; Acute Tox. 2, H330; ♦ Carc. 1B, H350; STOT RE 1, H372; → Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	< 0.3%
CAS: 7440-48-4 EINECS: 231-158-0 Index number: 027-001-00-9	cobalt ❖ Resp. Sens. 1, H334; Carc. 1B, H350; Repr. 1B, H360; ❖ Acute Tox. 4, H302; Skin Sens. 1, H317	< 0.3*%

<sup>•</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First-aid measures

#### 4.1 Description of first aid measures

#### After inhalation:

If metal vapours or solid dusts have been inhaled:

Get the affected person out in the fresh air and call a doctor.

#### After skin contact:

Foreign bodies which have penetrated the skin must be removed and the wound cleaned thoroughly.

#### After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Consult a doctor if the symptoms persist.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- Information for doctor: Beryllium, chronic lung diseases (berylliosis)
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.



(MSDS)

Reviewed on 01/09/2019 Printing date 01/09/2019 Version - No. 2

Trade name: MARVAC® 125

(Contd. of page 2)

#### 5 Fire-fighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

Non-combustible.

Extinguishing agents must be adapted to the environment.

• 5.2 Special hazards arising from the substance or mixture

Formation of toxic smoke / fumes (metal / metal oxides) is possible during heating or in case of fire. Do not inhale

- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

#### 6 Accidental release measures

Accidental release of dusts and vapours which are damaging to health can be ruled out.

- 6.1 Personal precautions, protective equipment and emergency procedures No special measures required.
- 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: No special measures required.
- 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

#### • 7.1 Precautions for safe handling

No safety precautions are necessary in the delivered form.

The appropriate industrial and environmental safety measures

must be taken for processing steps which cause dust

(see also section 8):

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

- Information about protection against explosions and fires: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- Storage class: Not applicable
- 7.3 Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

Additional information about design of technical systems:

Provide suction with filtering for good airing and ventilation of the work area during processing steps which cause dust. Air return is only permitted in exceptional cases.

If industrial vacuum cleaners are used, these must have dust class H (DIN EN 60335-2-69).

Suitable breathing apparatus must be used during repair and maintenance work to suction systems, especially when changing filters (see personal safety equipment).

(Contd. on page 4)



Printing date 01/09/2019 Version - No. 2 Reviewed on 01/09/2019

Trade name: MARVAC® 125

(Contd. of page 3)

#### • 8.1 Control parameters

7439-89-6 iro	on (compact form)	
	Long-term value: 1* 5** mg/m³	
,	as iron;*salts, water-soluble;**welding fume	
7440-47-3 ch	romium	
PEL (USA)	Long-term value: 1 mg/m³	
REL (USA)	Long-term value: 0.5* mg/m³	
TI \ ( (10 A)	*metal+inorg.compds.as Cr;See Pocket Guide App. C	
TLV (USA)	Long-term value: 0.003* 0.5** mg/m³ inh. fraction, *as Cr(III),**metal	
IOELV (EU)	Long-term value: 2 mg/m³ as Cr	
EL (Canada)	Long-term value: 0.5 mg/m³ as metal	
EV (Canada)	Long-term value: 0.05 mg/m³	
7440-02-0 nic	ckel	
PEL (USA)	Long-term value: 1 mg/m³	
REL (USA)	Long-term value: 0.015 mg/m³ as Ni; See Pocket Guide App. A	
TLV (USA)	Long-term value: 1.5* mg/m³ elemental, *inhalable fraction	
EL (Canada)	Long-term value: 0.05 mg/m³ ACGIH A1, IARC 2B	
EV (Canada)	Long-term value: 1 mg/m³ Inhalable fraction	
7439-98-7 mg	olybdenum	
PEL (USA)	Long-term value: 15* mg/m³ *Total dust, as Mo	
TLV (USA)	Long-term value: 10* 3** mg/m³ as Mo; *inhalable fraction ** respirable fraction	
EL (Canada)	Long-term value: 3* 10** mg/m³ as Mo; *respirable **inhalable	
EV (Canada)	Long-term value: 10* 3** 0.5*** mg/m³ metal,insol.compd.:*inh;**resp;sol.compd.:***resp	
7440-41-7 be	ryllium	
PEL (USA)	Short-term value: 0.002 mg/m³ Long-term value: 0.0002; 0.002* mg/m³ Ceiling limit value: 0.025*/** mg/m³, 0.005** ppm	
REL (USA)	as Be; *see 1910.1024; **30 min peak/8-hr shift Ceiling limit value: 0.0005 mg/m³ as Be; See Pocket Guide App. A	
TLV (USA)	Long-term value: 0.00005 mg/m³ as Be; inhalable; RSEN; soluble comp.: Skin, DSEN	
EL (Canada)	Long-term value: 0.00005 mg/m³ as Be; ACGIH A1, IARC 1; Skin, S(R); soluble: S(D)	
EV (Canada)	Short-term value: 0.01 mg/m³ Long-term value: 0.002 mg/m³ as Be; revoked as of 01/01/18	



(MSDS)

Reviewed on 01/09/2019 Printing date 01/09/2019 Version - No. 2

Trade name: MARVAC® 125

(Contd. of page 4)

7440-48-4 cobalt PEL (USA) Long-term value: 0.1\* mg/m3 as Co; \*for metal dust and fume REL (USA) Long-term value: 0.05 mg/m<sup>3</sup> as Co; metal dust & fume TLV (USA) Long-term value: (0.02) NIC-0.02\* mg/m3 \*inh. fraction; NIC-Skin, DSEN, RSEN, BEI EL (Canada) Long-term value: 0.02 mg/m<sup>3</sup> as Co; IARC 2B

#### • DNELs

**DNELs for OSH purposes** 

EV (Canada) Long-term value: 0.1 mg/m<sup>3</sup>

In Germany, occupational exposure limits (AGW) of the Technical Rules on Hazardous Substances (TRGS) 900 continue to constitute workplace atmospheric limit values that are binding upon employers. Should no AGW and for example no maximum workplace concentration (MAK value) of the German Research Foundation (DFG) be available, the employer must also consider the DNEL during risk assessment.

(Source: Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA)) current values are available: http://www.dguv.de/ifa/gestis/gestis-dnel-liste/index.jsp.

7440-02-0	7440-02-0 nickel				
Inhalative	Langzeitexposition - Inhalation - lokale Wirkung	0.05 mg/m³ (Ind)			
	Langzeitexposition - Inhalation - system. Wirkung	0.05 mg/m³ (Ind)			
7440-48-4	7440-48-4 cobalt				
Inhalative	Langzeitexposition - Inhalation - lokale Wirkung	0.04 mg/m³ (Ind)			
		0.0063 mg/m³ (Consumer)			

#### • Ingredients with biological limit values:

#### 7440-48-4 cobalt

BEI (USA) 15 µg/L

Medium: urine

Time: end of shift at end of workweek Parameter: Cobalt (background)

1 µg/L Medium: blood

Time: end of shift at end of workweek

Parameter: Cobalt (background, semi-quantitative)

#### Additional Occupational Exposure Limit Values for possible hazards during processing:

If the occurrence of chrome (VI) compounds cannot be ruled out, the TRGS 910 (acceptance and tolerance concentrations)

must be considered!

The AGW for nickel is to be used only for nickel metal.

For thermal processes in the presence of atmospheric oxygen, oxidic nickel compounds must always be assumed and the ERB (TRGS 910) must be applied.

#### • Additional information:

The lists that were valid during the creation were used as basis.

**GESTIS International Limit Values:** 

http://www.dguv.de/ifa/Gefahrstoffdatenbanken/GESTIS-Internationale-Grenzwerte-für-chemische-Substanzenlimit-values-for-chemical-agents/index.jsp

#### • 8.2 Exposure controls

#### • Personal protective equipment:

#### • General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

(Contd. on page 6)



Reviewed on 01/09/2019 Version - No. 2

Trade name: MARVAC® 125

Printing date 01/09/2019

(Contd. of page 5)

Store protective clothing separately. Do not eat, drink, smoke or sniff while working.

#### • Breathing equipment:



In the case of dust formation (limit value exceeded), breathing apparatus must be worn. Time limits for wearing must be observed.

Breathing mask, apparatus with particle filter P2 or P3, for example:

- Full face mask (EN 136)
- Breathing mask (EN 149) FFP2 or FFP3
- 10 times the limit value (FFP2)
- 30 times the limit value (FFP3)

Recommendation: P3

#### Protection of hands:



Avoid repeated and prolonged contact with the skin, use protective gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

#### Material of gloves

Experience has shown glove materials polychloroprene, nitrile caoutchouc, butyl caoutchouc, fluoride caoutchouc and polyvinylchloride to offer sufficient protection.

- Penetration time of glove material -
- Eye protection:



In the event of larger quantities of dust:

Wear protective glasses / EN 166, poss. with side protection.

#### • Limitation and supervision of exposure into the environment

The legal issue values and limitations are to be paid attention!

#### 9 Physical and chemical properties

• 9.1	l In	formati	ion oı	า bas	ic p	hysi	ical	and	С	hemi	ical	l propertie:	S
-------	------	---------	--------	-------	------	------	------	-----	---	------	------	--------------	---

General Information

Appearance:

Form: Semi-finished products/parts: e.g. strip, wire and parts

Color: Metallic • Odor: Odourless

• pH-value: Not applicable.

Change in condition

Melting point/Melting range (approx): 1 465 °C

Metting point/Metting range (approx): 1,400 C				
Auto igniting:	Not applicable			
<ul><li>Danger of explosion:</li></ul>	Not applicable			
Vapor pressure:	Not determined.			
<ul><li>Density (approx) at 20 °C:</li><li>Relative density</li></ul>	7.8 g/cm³ Not determined.			
Solubility in / Miscibility with				

Water: Insoluble.

(Contd. on page 7)



Trade name: MARVAC® 125

(Contd. of page 6)

• Partition coefficient (n-octanol/water): Not determined.

9.2 Other information
 No further relevant information available.

#### 10 Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions

Hydrogen is released in contact with acid which can cause explosive gas mixtures.

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values:

The following applies for the pure substances (here: nickel and beryllium):

	•				
7440-02-0	nickel				
Oral	LD50	>9,000 mg/kg (rat)			
7440-41-7	beryllium				
Inhalative	LC50/4 h	≤0.25 mg/l (rat)			
		für Aerosole oder Stäube			
7440-48-4	7440-48-4 cobalt				
Oral	LD50	550 mg/kg (rat)			
Inhalative	LC50/4 h	mg/l (rat)			
		siehe zusätzlicher toxikologischer Hinweis / see additional toxicological information			

- Primary irritant effect:
- on the skin: see sensitization
- on the eye:

Irritation of the eyes in the case of massive direct contact will be mainly due to mechanical effects depending on the grain size.

Sensitization:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- Additional toxicological information: --
- Carcinogenic categories

• IARC (International Agency for Research on Cancer)			
7440-47-3	chromium	3	
7440-02-0	nickel	2B	
7440-41-7	beryllium	1	
7440-48-4	cobalt	2B	

#### NTP (National Toxicology Program)

7440-02-0 nickel R

(Contd. on page 8)



(IIIODO)

Printing date 01/09/2019 Version - No. 2 Reviewed on 01/09/2019

Trade name: MARVAC® 125

		(Contd. of page 7)
7440-41-7	beryllium	K
7440-48-4	cobalt	R
• OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

#### 12 Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Alloys in solid form do not pose an ecological threat.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- 13.1 Waste treatment methods
- Recommendation: Observe offical regulations.
- Uncleaned packagings: Not applicable

#### 14 Transport information

- Transport/Additional information:
- ADR
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Maritime transport IMDG:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Air transport ICAO-TI and IATA-DGR
- Remarks: Non-hazardous goods from the standpoint of the specified regulations

#### 15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Information about limitation of use:

Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

--

- Technical instructions (air): The emission values and limitations must be observed!
- Water hazard class: Alloys in solid form do not pose an ecological threat.

(Contd. on page 9)



Version - No. 2 Reviewed on 01/09/2019

Trade name: MARVAC® 125

Printing date 01/09/2019

(Contd. of page 8)

#### Other regulations, limitations and prohibitive regulations

e.a

- 1272/2008/EG (CLP)

- 1907/2006/EG (REACH)
- German Hazardous Substances
- 15.2 Chemical safety assessment: Void (for articles)

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

Wording of the hazard warnings mentioned (Chapter 3) for pure substances:

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H350 May cause cancer. Route of exposure: Inhalation.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

#### Department issuing SDS:

Department OPS-C SE Tel. 06181/38-2045

#### • Contact:

**Environmental Protection Department** 

Tel. 06181/38-2359

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 1B: Carcinogenicity – Category 1B Carc. 2: Carcinogenicity – Category 2

Repr. 1A: Reproductive toxicity – Category 1A

(Contd. on page 10)





Printing date 01/09/2019 Version - No. 2 Reviewed on 01/09/2019

Trade name: MARVAC® 125

(Contd. of page 9)

Repr. 1B: Reproductive toxicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

- KÜHN-BIRETT-Merkblätter gefährlicher Arbeitsstoffe
- Technische Regeln für Gefahrstoffe