

Material Safety Data Sheet

(MSDS)

Printing date 04/05/2013

Version - No. 2

Reviewed on 04/05/2013

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:**
Permanent magnet, coated with aluminium
VACODYM®
- **Article number:**
VACODYM 100-199, 300-399, 400-499, 500-599, 710-799, 810-899, 900-999, 4317 und 4514
(all qualities)
- ® registered trademark of VACUUMSCHMELZE GmbH & Co. KG
- **Material Safety Data Sheet - no.:** IB77
- **Relevant identified uses of the substance or mixture and uses advised against** Not applicable
- **Application of the substance / the preparation**
PERMANENT MAGNETS e.g. in motors, generators, sensors, E-Mobility
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
VACUUMSCHMELZE GmbH & Co.KG
Grüner Weg 37
D-63450 Hanau
- datasheet@vacuumschmelze.com
- **Information department:** Environmental Protection Department
- **Emergency telephone number:**
Tel. no.: (**49) 6181/38-0
Emergency tel. no.: via (**49) 6181/38-0

2 Hazards identification

- **Classification (substance or mixture)**
Classification according to Regulation (EC) No 1272/2008 (CLP-Regulation):
Not applicable
Our semi-finished and finished products constitute manufactured articles under the terms of the REACH Regulation (EC) No. 1907/2006.
For articles there is no obligation to classify acc. to CLP -Regulation.
- **Labelling according to Regulation (EC) No 1272/2008**
Labelling according to Regulation (EC) No 1272/2008 (CLP-Regulation):
Not applicable
The product is classified and labelled according to the CLP regulation.
- **Additional VAC information:**
The following applies to the permanent magnet:
Contains Cobalt. May produce an allergic reaction.
In the case of dust-producing processing, we recommend observance of the following warnings :
The hazard statements result from the ingredients (composition) of the permant magnets and the applied coating.
- **Hazard statements**
See also 'Other hazards'
Causes skin irritation.
Causes serious eye irritation.
- **Precautionary statements**
Do not breathe dust/fume/gas/mist/vapours/spray.
In case of inadequate ventilation wear respiratory protection.
Use personal protective equipment as required.
Avoid release to the environment.
Take off contaminated clothing and wash before reuse.
If skin irritation occurs: Get medical advice/attention.

(Contd. on page 2)

Material Safety Data Sheet

(MSDS)

Printing date 04/05/2013

Version - No. 2

Reviewed on 04/05/2013

Trade name: **VACODYM®**

(Contd. of page 1)

• Other hazards

Dry mechanical processing of rare earth permanent magnet alloys is only permitted under special safety precautions because dusts which are capable of self-heating or pyrophorous dusts with a tendency to explode may be produced.

In the case of wet mechanical processing the watery processing medium reacts with the magnet wear and may form hydrogen already at room temperature.

Attention: Formation of Ex-atmospheres possible!

Part of the resulting hydrogen is stored in the material.

The resulting processing sludges must be kept under a protective liquid because drying out sludges are capable of self-heating or

may react pyrophorously. In this case the stored hydrogen volume burns off with flames.

Attention:

Magnetized parts generate magnetic fields and are able to attract magnetizable materials. This may result in injury during handling of magnets.

Electronic devices and measuring tools may be changed in calibration or damaged by the high magnetic field strength.

Please keep magnetized magnets away from computers, displays and magnetic storage devices. Especially people with heart pacemakers must keep away from magnetic fields.

• Results of PBT and vPvB assessment

• PBT: Not applicable.

• vPvB: Not applicable.

3 Composition/information on ingredients

• Chemical characterization:

• Description: Coated permanent-magnet in compact form

• Dangerous components:

The classifications given below reflect the classification of each pure substance respectively and are intended for information only

CAS: 7439-89-6 EINECS: 231-096-4	iron	rest%
CAS: 7440-00-8 EINECS: 231-109-3	neodymium (powder) ☒ Xi R36/38; ☒ F R11 R53 ☒ Flam. Sol. 2, H228; ☒ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	*%
CAS: 7429-91-6 EINECS: 231-073-9	dysprosium (powder) ☒ Xi R36/38; ☒ F R11 R53 ☒ Flam. Sol. 2, H228; ☒ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	*%
CAS: 7440-10-0	praseodymium (powder) ☒ Xi R36/38; ☒ F R11 R53 ☒ Flam. Sol. 2, H228; ☒ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	*%
CAS: 7440-27-9 EINECS: 231-137-6	terbium (powder) ☒ Xi R36/38; ☒ F R11 R53 ☒ Flam. Sol. 2, H228; ☒ Skin Irrit. 2, H315; Eye Irrit. 2A, H319	*%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-001-00-6	aluminium ☒ F R15-17 ☒ Pyr. Sol. 1, H250; Water-react. 2, H261	coating%

• Remark to the composition:

* The total maximum proportion of rare earths (neodymium, dysprosium, praseodymium and/or terbium) is 35%.

To improve the corrosion resistance an additional chromating containing chromium (III), chromium (VI) can be used.

• Additional information:

For the rare earths listed here, the following apply:

(Contd. on page 3)

Material Safety Data Sheet

(MSDS)

Printing date 04/05/2013

Version - No. 2

Reviewed on 04/05/2013

Trade name: VACODYM®

(Contd. of page 2)

- Classification as per CLP notification (VAC).
- The classifications listed refer exclusively to powder form.
- The rare earths specified are classified as NON-hazardous in solid form.

4 First aid measures

- **Description of first aid measures**
- **After inhalation:**
If metal vapours or solid dusts have been inhaled:
Get the affected person out in the fresh air and call a doctor.
- **After skin contact:**
Foreign bodies which have penetrated the skin must be removed and the wound cleaned thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Consult a doctor if the symptoms persist.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Non-combustible.
Extinguishing agents must be adapted to the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

Accidental release of dusts and vapours which are damaging to health can be ruled out.

- **Personal precautions, protective equipment and emergency procedures** No special measures required.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:** No special measures required.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No protective measures are required in the provided form.
Dry mechanical processing of rare earth permanent magnet alloys is only permitted under special safety precautions because dusts which are capable of self-heating or pyrophorous dusts with a tendency to explode may be produced.
In the case of wet mechanical processing the watery processing medium reacts with the magnet wear and may form hydrogen already at room temperature.
Attention: Formation of Ex-atmospheres possible!
Part of the resulting hydrogen is stored in the material.
The resulting processing sludges must be kept under a protective liquid because drying out sludges are capable of self-heating or

(Contd. on page 4)

Material Safety Data Sheet

(MSDS)

Printing date 04/05/2013

Version - No. 2

Reviewed on 04/05/2013

Trade name: VACODYM®

(Contd. of page 3)

may react pyrophorously. In this case the stored hydrogen volume burns off with flames.
Also see section 8.

- **Information about protection against explosions and fires:**
No particular measures are required in the provided form.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
Keep magnetized magnets away from computers, displays and magnetic storage devices. Especially people with heart pacemakers must keep away from magnetic fields.
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class:** Not applicable
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:**
Provide a suitable suction with filter and good ventilation of the working area for all processing steps.

Suitable breathing apparatus must be used (see personal safety equipment) for repair and maintenance work on suction systems, especially when changing the filters.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

7439-89-6 iron	
EV (Canada)	1* 5** mg/m ³ as iron;*salts, water-soluble;**welding fume
7429-90-5 aluminium	
EL (Canada)	1.0 mg/m ³ metal and insoluble compounds, respirable
EV (Canada)	5 mg/m ³ aluminium-containing (as aluminium)
PEL (USA)	15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	10* 5** mg/m ³ Metal, insol.compds.:*total dust**resp. fraction
TLV (USA)	1* mg/m ³ *as respirable fraction

- **Additional Occupational Exposure Limit Values for possible hazards during processing:**
If the occurrence of chrome (VI) compounds cannot be ruled out, the appropriate workplace-related limit values must also be monitored!
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

(Contd. on page 5)

Material Safety Data Sheet
(MSDS)

Printing date 04/05/2013

Version - No. 2

Reviewed on 04/05/2013

Trade name: **VACODYM**[®]

(Contd. of page 4)

• **Breathing equipment:**



In the case of dust formation (limit value exceeded), breathing apparatus must be worn. Time limits for wearing must be observed.

Breathing mask, apparatus with particle filter P1 or P2, for example:

- Breathing mask (EN 149) FFP1 or FFP2
4 times the limit value (FFP1)
10 times the limit value (FFP2)

A

- Full-face mask (EN 136) or a
- Breathing mask (EN 149) FFP3
30 times the limit value

is recommended for chromium (III) and chromium (VI) dusts.

• **Protection of hands:**



Avoid repeated and prolonged contact with the skin, use protective gloves.

Repeated and extended skin contact with chromated permanent magnet alloys is to be avoided; wear safety gloves.

Preventive skin protection by use of skin-protecting agents is recommended.

• **Material of gloves**

Experience has shown glove materials polychloroprene, nitrile caoutchouc, butyl caoutchouc, fluoride caoutchouc and polyvinylchloride to offer sufficient protection.

Experience has shown glove materials polychloroprene, nitrile caoutchouc, butyl caoutchouc, fluoride caoutchouc and polyvinylchloride to offer sufficient protection.

• **Penetration time of glove material -**

• **Eye protection:**



Safety goggles / EN 166, with side shields if necessary, must be worn in dusty environments and when working with magnetised magnets (> 50 g).

• **Limitation and supervision of exposure into the environment**

The legal issue values and limitations are to be paid attention!

9 Physical and chemical properties

• **Information on basic physical and chemical properties**

General Information

The physical and chemical properties of this section refer to the unplated permanent magnet alloy.

No values are available for the coating itself.

• **Appearance:**

Form:

Parts

Color:

Metallic

• **Odor:**

Odourless

• **pH-value:**

Not applicable.

• **Change in condition**

Melting point/Melting range (approx): 1180 °C

• **Auto igniting:**

Omitted (in the provided form).
Also see section 2 and/or 7.

• **Danger of explosion:**

Omitted (in the provided form).
Also see section 2 and/or 7.

• **Vapor pressure:**

Not determined.

• **Density (approx) at 20 °C:**

7.5 g/cm³

(Contd. on page 6)

Material Safety Data Sheet

(MSDS)

Printing date 04/05/2013

Version - No. 2

Reviewed on 04/05/2013

Trade name: **VACODYM®**

(Contd. of page 5)

• Relative density	Not determined.
• Solubility in / Miscibility with Water:	Insoluble.
• Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
Hydrogen is released in contact with acid which can cause explosive gas mixtures.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:**
Irritant to skin and mucous membranes.
Rare earths (see list in Section 2) cause skin irritation depending on grain size (powder) (Skin Irrit. 2)
- **on the eye:**
Rare earths (see list in Section 2) cause eye irritation depending on grain size (powder) (Eye Irrit. 2)
- **Sensitization:**
It is possible that sensibilization develops if the surface is chromated and if repeated and extended skin contact with this chromated surface occurs.
The following applies to the permanent magnet:
Contains Cobalt. May produce an allergic reaction.
- **Subacute to chronic toxicity:**

Chromium trioxide in the form of inhalable dusts is classified as category 2 carcinogenic.
Definition/category 2: "Substances which can be considered as causing cancer in humans."
Related to the pure substance there is enough evidence to assume that human exposure to the substance can cause cancer. This assumption is based generally on the following:
- suitable long-term experiments with animals
- other relevant information
- **Additional toxicological information:**
When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 7)

Material Safety Data Sheet

(MSDS)

Printing date 04/05/2013

Version - No. 2

Reviewed on 04/05/2013

Trade name: **VACODYM®**

(Contd. of page 6)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Observe official regulations.
- **Uncleaned packagings:** Not applicable

14 Transport information

- **Transport/Additional information:**
- **Land transport DOT / TDG**
- **Remarks:** Non-hazardous goods from the standpoint of the specified regulations
Attention: Packing boxes with magnetized parts inside generate magnetic fields and are able to attract magnetizable materials.

- **Maritime transport IMDG:**
- **Remarks:** Non-hazardous goods from the standpoint of the specified regulations
Attention: Packing boxes with magnetized parts inside generate magnetic fields and are able to attract magnetizable materials.

- **Air transport ICAO-TI and IATA-DGR** **Non-magnetised parts:**
Not classified as hazardous goods as understood in the ordinance given

Magnetised parts in packaging units:
Conduct test for classification as per IATA regulations (see Class 9 / Packing Instruction 902)

If test is positive, the following apply:
ICAO/IATA class: Class 9 / Page 172
UN/ID number: 2807
Correct technical name: Magnetised materials
- **Remarks:** -

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

• **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

• **Section 313 (Specific toxic chemical listings):**

7429-90-5 | aluminium

• **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

(Contd. on page 8)

Material Safety Data Sheet

(MSDS)

Printing date 04/05/2013

Version - No. 2

Reviewed on 04/05/2013

Trade name: **VACODYM®**

(Contd. of page 7)

• Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

• Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

• Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

• Cancerogenity categories

• EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

7429-90-5	aluminium	A4
-----------	-----------	----

• MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

• National regulations:

• Other regulations, limitations and prohibitive regulations

- e.g.
- guidelines 67/548/ECC, 1999/45/EC
 - 1272/2008/EG (CLP)
 - 1907/2006/EG (REACH)
 - German Hazardous Substances

• please note:

Attention:
 Magnetized parts generate magnetic fields and are able to attract magnetizable materials. This may result in injury during handling of magnets.
 Electronic devices and measuring tools may be changed in calibration or damaged by the high magnetic field strength.
 Please keep magnetized magnets away from computers, displays and magnetic storage devices. Especially people with heart pacemakers must keep away from magnetic fields.

• Chemical safety assessment: Void (for articles)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant phrases

Wording of safety instructions quoted (Section 3) concerning pure substances (powder):

- H228 Flammable solid.
- H250 Catches fire spontaneously if exposed to air.
- H261 In contact with water releases flammable gas.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- R11 Highly flammable.
- R15 Contact with water liberates extremely flammable gases.
- R17 Spontaneously flammable in air.
- R36/38 Irritating to eyes and skin.
- R53 May cause long-term adverse effects in the aquatic environment.

(Contd. on page 9)

Material Safety Data Sheet
(MSDS)

Printing date 04/05/2013

Version - No. 2

Reviewed on 04/05/2013

Trade name: **VACODYM**[®]

(Contd. of page 8)

• **Department issuing MSDS:**

Department HT-F
Tel. 06181/38-2045

• **Contact:**

Environmental Protection Department
Tel. 06181/38-2359

• **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists

• **Sources**

- KÜHN-BIRETT-Merkblätter gefährlicher Arbeitsstoffe
- Technische Regeln für Gefahrstoffe

• *** Data compared to the previous version altered.**

USA