VACUUMSCHMELZE

Material Safety Data Sheet

(MSDS)

Version - No. 2

Reviewed on 01/10/2019

1 Identification

Printing date 01/10/2019

- •1.1 Product identifier
- Trade name: DURACON 17 A®
- Article number:

® registered trademark of VACUUMSCHMELZE GmbH & Co. KG

- Material Safety Data Sheet no.: SDB90
- Application of the substance / the mixture semi-finished products and parts
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: VACUUMSCHMELZE GmbH & Co.KG Grüner Weg 37 D-63450 Hanau

datasheet@vacuumschmelze.com

- Information department: Environmental Protection Department
- **1.4 Emergency telephone number:** Tel. no.: (**49) 6181/38-0 Emergency tel. no.: via (**49) 6181/38-0

2 Hazard(s) identification

2.2 Classification (substance or mixture) Classification according to Regulation (EC) No 1272/2008 (CLP-Regulation): Not applicable Our semi-finished and finished products constitute manufactured articles under the terms of the REACH Regulation (EC) No. 1907/2006. For articles there is no obligation to classify acc. to CLP -Regulation. 2.2 Labelling according to Regulation (EC) No 1272/2008 Labelling according to Regulation (EC) No 1272/2008 (CLP-Regulation): Not applicable • Additional VAC information: In the case of dust-producing processing, we recommend observance of the following warnings : Hazard statements May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer. Route of exposure: Inhalation. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Precautionary statements Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Avoid release to the environment. Use personal protective equipment as required. In case of inadequate ventilation wear respiratory protection. Get medical advice/attention if you feel unwell. • 2.3 Other hazards • Results of PBT and vPvB assessment • PBT: Not applicable. • vPvB: Not applicable. USA

(Contd. on page 2)

(MSDS)

Version - No. 2

Reviewed on 01/10/2019

Trade name: DURACON 17 A[®]

(Contd. of page 1)

3 Composition/information on ingredients

- 3.2 Chemical characterization:
- Description: Metal in compact form
- Dangerous components:

The classifications given below reflect the classification of each pure substance respectively and are intended for information only

The legal classifications of the pure substances (harmonized classification according to substance list of the Annex VI of the CLP Regulation) got complemented, insofar as additional substance-specific information from accessible data sources (e.g. TRGS 905, toxicological studies) for health hazards and / or physical hazards are available.

CAS: 7439-89-6 EINECS: 231-096-4	iron (compact form)	rest%
CAS: 7440-02-0 EINECS: 231-111-4 Index number: 028-002-00-7	nickel	~ 28%
CAS: 7440-48-4 EINECS: 231-158-0 Index number: 027-001-00-9	cobalt	~ 17%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

Additional information for Cobalt:

See also Chapter 11

4 First-aid measures

4.1 Description of first aid measures

• After inhalation:

If metal vapours or solid dusts have been inhaled: Get the affected person out in the fresh air and call a doctor.

• After skin contact:

Foreign bodies which have penetrated the skin must be removed and the wound cleaned thoroughly.

• After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Consult a doctor if the symptoms persist.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: Non-combustible.
- Extinguishing agents must be adapted to the environment.
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic smoke / fumes (metal / metal oxides) is possible during heating or in case of fire. Do not inhale fumes.

(Contd. on page 3)



⁻ USA

(MSDS)

Version - No. 2

Reviewed on 01/10/2019

Trade name: DURACON 17 A[®]

(Contd. of page 2)

- 5.3 Advice for firefighters
- Protective equipment: No special measures required.

6 Accidental release measures

Accidental release of dusts and vapours which are damaging to health can be ruled out.

6.1 Personal precautions, protective equipment and emergency procedures No special measures required.

- 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: No special measures required.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

7.1 Precautions for safe handling

No safety precautions are necessary in the delivered form. The appropriate industrial and environmental safety measures must be taken for processing steps which cause dust (see also section 8): Prevent formation of dust. Ensure good ventilation/exhaustion at the workplace. Take note of emission threshold.

• Information about protection against explosions and fires: No special measures required.

•7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- Storage class: Not applicable
- •7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems:

Provide suction with filtering for good airing and ventilation of the work area during processing steps which cause dust. Air return is only permitted in exceptional cases.

If industrial vacuum cleaners are used, these must have dust class H (DIN EN 60335-2-69).

Suitable breathing apparatus must be used during repair and maintenance work to suction systems, especially when changing filters (see personal safety equipment).

• 8.1 Control parameters

· Components with limit values that require monitoring at the workplace:

7439-89-6 iron (compact form)

EV (Canada) Long-term value: 1* 5** mg/m³ as iron;*salts, water-soluble;**welding fume

(Contd. on page 4)

USA



Version - No. 2

Reviewed on 01/10/2019

Trade name: DURACON 17 A®

7440-02-0 ni		(Contd. of pag			
PEL (USA)	Long-term value: 1 mg/m ³				
REL (USA)	Long-term value: 0.015 mg/m ³ as Ni; See Pocket Guide App. A				
TLV (USA)	Long-term value: 1.5* mg/m ³ elemental, *inhalable fraction				
EL (Canada)	Long-term value: 0.05 mg/m ³ ACGIH A1, IARC 2B				
EV (Canada)	Long-term value: 1 mg/m ³ Inhalable fraction				
7440-48-4 co	obalt				
PEL (USA)	Long-term value: 0.1* mg/m ³ as Co; *for metal dust and fume				
REL (USA)	Long-term value: 0.05 mg/m ³ as Co; metal dust & fume				
TLV (USA)	Long-term value: (0.02) NIC-0.02* mg/m³ *inh. fraction; NIC-Skin, DSEN, RSEN, BEI				
EL (Canada)	Long-term value: 0.02 mg/m ³ as Co; IARC 2B				
EV (Canada)	Long-term value: 0.1 mg/m ³				
continue to c for example available, the (Source: Inst	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK value) e employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich	en Unfallversicherung (IFA))			
continue to c for example available, the (Source: Inst	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK value e employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/ge	at are binding upon employers. Should no AGW a lue) of the German Research Foundation (DFG) b risk assessment. en Unfallversicherung (IFA))			
continue to c for example available, the (Source: Inst current value 7440-02-0 n	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK value e employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/ge	at are binding upon employers. Should no AGW a lue) of the German Research Foundation (DFG) b risk assessment. en Unfallversicherung (IFA))			
continue to c for example available, the (Source: Inst current value 7440-02-0 ni Inhalative La	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK value e employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/ge ickel	at are binding upon employers. Should no AGW at lue) of the German Research Foundation (DFG) by prisk assessment. en Unfallversicherung (IFA)) estis-dnel-liste/index.jsp. 0.05 mg/m³ (Ind)			
continue to c for example available, the (Source: Inst current value 7440-02-0 ni Inhalative La	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK values e employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/ge ickel angzeitexposition - Inhalation - lokale Wirkung angzeitexposition - Inhalation - system. Wirkung	at are binding upon employers. Should no AGW at lue) of the German Research Foundation (DFG) by prisk assessment. en Unfallversicherung (IFA)) estis-dnel-liste/index.jsp. 0.05 mg/m³ (Ind)			
continue to c for example available, the (Source: Inst current value 7440-02-0 ni Inhalative La 2440-48-4 c	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK values e employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/ge ickel angzeitexposition - Inhalation - lokale Wirkung angzeitexposition - Inhalation - system. Wirkung	at are binding upon employers. Should no AGW at lue) of the German Research Foundation (DFG) by prisk assessment. en Unfallversicherung (IFA)) estis-dnel-liste/index.jsp. 0.05 mg/m³ (Ind)			
continue to c for example available, the (Source: Inst current value 7440-02-0 ni Inhalative La 7440-48-4 co Inhalative La	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK value e employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/ge ickel angzeitexposition - Inhalation - lokale Wirkung angzeitexposition - Inhalation - system. Wirkung obalt	at are binding upon employers. Should no AGW at lue) of the German Research Foundation (DFG) by risk assessment. en Unfallversicherung (IFA)) estis-dnel-liste/index.jsp. 0.05 mg/m ³ (Ind) 0.05 mg/m ³ (Ind) 0.04 mg/m ³ (Ind)			
continue to c for example available, the (Source: Inst current value 7440-02-0 ni Inhalative La 7440-48-4 co Inhalative La	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK value e employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/ge ickel angzeitexposition - Inhalation - lokale Wirkung angzeitexposition - Inhalation - system. Wirkung obalt angzeitexposition - Inhalation - lokale Wirkung with biological limit values:	at are binding upon employers. Should no AGW at lue) of the German Research Foundation (DFG) by risk assessment. en Unfallversicherung (IFA)) estis-dnel-liste/index.jsp. 0.05 mg/m ³ (Ind) 0.05 mg/m ³ (Ind) 0.04 mg/m ³ (Ind)			
continue to c for example i available, the (Source: Inst current value 7440-02-0 ni Inhalative La 7440-48-4 cc Inhalative La Ingredients 7440-48-4 cc BEI (USA) 1 N T F	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK values the employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/gr ickel angzeitexposition - Inhalation - lokale Wirkung angzeitexposition - Inhalation - system. Wirkung obalt angzeitexposition - Inhalation - lokale Wirkung with biological limit values: obalt 5 μg/L /dedium: urine ime: end of shift at end of workweek Parameter: Cobalt (background)	at are binding upon employers. Should no AGW at lue) of the German Research Foundation (DFG) by risk assessment. en Unfallversicherung (IFA)) estis-dnel-liste/index.jsp. 0.05 mg/m ³ (Ind) 0.05 mg/m ³ (Ind) 0.04 mg/m ³ (Ind)			
continue to c for example i available, the (Source: Inst current value 7440-02-0 ni Inhalative La 7440-48-4 cc Inhalative La BEI (USA) 1 N T F	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK values the employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/gr ickel angzeitexposition - Inhalation - lokale Wirkung angzeitexposition - Inhalation - system. Wirkung obalt angzeitexposition - Inhalation - lokale Wirkung obalt 5 μg/L /edium: urine ime: end of shift at end of workweek	at are binding upon employers. Should no AGW at lue) of the German Research Foundation (DFG) by prisk assessment. en Unfallversicherung (IFA)) estis-dnel-liste/index.jsp. 0.05 mg/m³ (Ind) 0.05 mg/m³ (Ind) 0.0063 mg/m³ (Consumer)			
continue to c for example available, the (Source: Inst current value 7440-02-0 ni Inhalative La 7440-48-4 cd Inhalative La 7440-48-4 cd BEI (USA) 1 M T BEI (USA) 1 M T F Additional C	constitute workplace atmospheric limit values the no maximum workplace concentration (MAK values the employer must also consider the DNEL during titut für Arbeitsschutz der Deutschen Gesetzlich es are available: http://www.dguv.de/ifa/gestis/ge ickel angzeitexposition - Inhalation - lokale Wirkung angzeitexposition - Inhalation - system. Wirkung obalt angzeitexposition - Inhalation - lokale Wirkung obalt 5 μg/L /dedium: urine Time: end of shift at end of workweek Parameter: Cobalt (background) μg/L /dedium: blood Time: end of shift at end of workweek	at are binding upon employers. Should no AGW at lue) of the German Research Foundation (DFG) be grisk assessment. en Unfallversicherung (IFA)) estis-dnel-liste/index.jsp. 0.05 mg/m³ (Ind) 0.05 mg/m³ (Ind) 0.04 mg/m³ (Ind) 0.0063 mg/m³ (Consumer)			



(MSDS)


Version - No. 2

Reviewed on 01/10/2019

Trade name: DURACON 17 A®

Printing date 01/10/2019

• pH-value:



Not applicable.

(Contd. on page 6)

- USA -

(MSDS)

Version - No. 2

Reviewed on 01/10/2019

Trade name: DURACON 17 A®

		(Contd. of page 5)	
• Change in condition Melting point/Melting range (approx): 1,400-1,500 °C			
• Auto igniting:	Not applicable		
Danger of explosion:	Not applicable		
Vapor pressure:	Not determined.		
 Density (approx) at 20 °C: Relative density 	8.3 g/cm ³ Not determined.		
 Solubility in / Miscibility with Water: 	Insoluble.		
 Partition coefficient (n-octanol/water): 9.2 Other information 	Not determined. No further relevant information available.		

10 Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions
- Hydrogen is released in contact with acid which can cause explosive gas mixtures.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values:

The following applies for the pure substances:

Oral LD50 >9,000 mg/kg (rat) 7440-48-4 cobalt Oral LD50 550 mg/kg (rat) Inhalative LC50/4 h mg/l (rat) Intervention of the second secon	7440-02-0 nickel		
Oral LD50 550 mg/kg (rat) Inhalative LC50/4 h mg/l (rat)	Oral	LD50	>9,000 mg/kg (rat)
Inhalative LC50/4 h mg/l (rat)	7440-48-4 cobalt		
	Oral	LD50	550 mg/kg (rat)
	Inhalative	LC50/4 h	mg/l (rat)
siene zusatzlicher toxikologischer Hinweis / see additional toxicological information			siehe zusätzlicher toxikologischer Hinweis / see additional toxicological information

• Primary irritant effect:

- on the skin: see sensitization
- on the eye:

Irritation of the eyes in the case of massive direct contact will be mainly due to mechanical effects depending on the grain size.

Sensitization:

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Additional toxicological information:

Subsequent users should be aware of the fact that Co-metal fine powder are classified as "acute toxic if inhaled, Category 1" (no legal classification); LC50 4hr \leq 0,05 mg/l.

(Contd. on page 7)



(MSDS)

Version - No. 2

Reviewed on 01/10/2019

Trade name: DURACON 17 A[®]

(Contd. of page 6) In case the subsequent use of product generates fine Co-metal particles (e.g. dust), protection measures such as described in Chapter 7 and 8 of this information sheet must be applied.

• Carcinogenic categories

IARC (International Agency for Research on Cancer)

7440-02-0 nickel 7440-48-4 cobalt

NTP (National Toxicology Program)

7440-02-0 nickel

7440-48-4 cobalt

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

12.1 Toxicity


- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- •12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Alloys in solid form do not pose an ecological threat.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- 13.1 Waste treatment methods
- Recommendation: Observe offical regulations.
- Uncleaned packagings: Not applicable

14 Transport information

- Transport/Additional information:
- ADR
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Maritime transport IMDG:
- Remarks: Non-hazardous goods from the standpoint of the specified regulations
- Air transport ICAO-TI and IATA-DGR
- Remarks: Non-hazardous goods from the standpoint of the specified regulations





Printing date 01/10/2019

2B

2B

R

R

(MSDS)

Version - No. 2

Reviewed on 01/10/2019

Trade name: DURACON 17 A[®]

(Contd. of page 7)

15 Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Information about limitation of use:

Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- Technical instructions (air): The emission values and limitations must be observed!
- Water hazard class: Alloys in solid form do not pose an ecological threat.

• Other regulations, limitations and prohibitive regulations

- e.g.
- 1272/2008/EG (CLP)
- 1907/2006/EG (REACH)
- German Hazardous Substances
- 15.2 Chemical safety assessment: Void (for articles)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

Wording of the hazard warnings mentioned (Chapter 3) for pure substances:

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350 May cause cancer. Route of exposure: Inhalation.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

• Department issuing SDS:

Department OPS-C SE Tel. 06181/38-2045

• Contact:

Environmental Protection Department Tel. 06181/38-2359

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

(Contd. on page 9)



USA

Version - No. 2

Reviewed on 01/10/2019

Trade name: DURACON 17 A[®]

Printing date 01/10/2019

(Contd. of page 8)

USA

BEI: Biological Exposure Limit Acute Tox. 4: Acute toxicity – Category 4 Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Carc. 1B: Carcinogenicity – Category 1B Carc. 2: Carcinogenicity – Category 2 Repr. 1A: Reproductive toxicity – Category 1A Repr. 1B: Reproductive toxicity – Category 1B STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Sources

- KÜHN-BIRETT-Merkblätter gefährlicher Arbeitsstoffe

- Technische Regeln für Gefahrstoffe

